





















**CẦU DAO TỰ ĐỘNG MCCB
MOULDED CASE CIRCUIT BREAKER**






Frame size (AF)			50	100	100	100
Model			NF50-CM	NF100-CM	NF100-SM	NF100-HM
Apperance						
Rated current In (A) at ambient temp. 40°C			15,20,30,40, 50	15,20,30,40, 50,60,75,100	15,20,30,40, 50,60,75,100	15,20,30,40, 50,60,75,100
Rate Insulation Voltage Ui (V)			690	690	690	690
Number of poles (P)			3	3	3 4	3 4
Rated breaking capacity (kA)	IEC 60947-2 EN 60947-2 CNS 14816-2 Icu/lcs AC	440V	2.5/1.3	7.5/3.8	10/5	25/13
		380V	2.5/1.3	7.5/3.8	15/7.5	30/15
		220V	5/2.5	10/5	25/13	50/25
Dimension (mm)		a	75	75	75 100	75 100
		b	130	130	130	130
		c	64	64	64	62
		ca	84	84	84	85
		bb	110	110	110	111
		aa	25	25	25 50	23 50
		d	4.5	4.5	4.5	4.5
Frame size (AF)			100	125	250	250
Model			NF100-UM	NF125-SM	NF250-CM	NF250-SM
Apperance						
Rated current In (A) at ambient temp. 40°C			15,20,30,40, 50,60,75,100	15,20,30,40, 50,60,75,100, 125	125,150,175, 200,225,250	125,150,175, 200,225,250
Rate Insulation Voltage Ui (V)			800	690	800	800
Number of poles (P)			3	3	3	3 4
Rated breaking capacity (kA)	IEC 60947-2 EN 60947-2 CNS 14816-2 Icu/lcs AC	440V	42/21	15/7.5	15/7.5	25/13
		380V	50/25	22/11	22/11	30/15
		220V	85/43	30/15	30/15	50/25
Dimension (mm)		a	92	75	107	107 142
		b	150	130	165	165
		c	86	64	87	87
		ca	104	84	114	114
		bb	129	110	126	126
		aa	30	25	35	35 70
		d	4.5	4.5	4.5	4.5

**CẦU ĐẠO TỰ ĐỘNG MCCB
MOULDED CASE CIRCUIT BREAKER**

Frame size (AF)			250	250	400	400
Model			NF250-HM	NF250-UM	NF400-CM	NF400-SM
Apperance						
Rated current In (A) at ambient temp. 40°C			125,150,175, 200,225,250	125,150,175, 200,225,250	250,300,350, 400	250,300,350, 400
Rate Insulation Voltage Ui (V)			800	800	800	800
Number of poles (P)			3 4	3	3	3 4
Rated breaking capacity (kA)	IEC 60947-2 EN 60947-2 CNS 14816-2 Icu/Ics AC	440V	30/15	42/21	22/11	30/15
		380V	36/18	50/25	25/13	35/18
		220V	50/25	85/43	35/18	50/25
Dimension (mm)		a	107 142	107	150	150 198
		b	165	165	257	257
		c	87	104	107.5	107.5
		ca	114	128	151.5	151.5
		bb	126	126	194	194
		aa	35 70	35	44	44 88
		d	4.5	4.5	7	7

Frame size (AF)			400	630	630	800
Model			NF400-HM	NF630-SM	NF630-HM	NF800-CM
Apperance						
Rated current In (A) at ambient temp. 40°C			250,300,350, 400	500,630	500,630	700,800
Rate Insulation Voltage Ui (V)			800	800	800	800
Number of poles (P)			3 4	3 4	3 4	3
Rated breaking capacity (kA)	IEC 60947-2 EN 60947-2 CNS 14816-2 Icu/Ics AC	440V	42/21	30/15	42/21	30/15
		380V	50/25	35/18	50/25	35/18
		220V	85/43	50/25	85/43	50/25
Dimension (mm)		a	150 198	181 240	181 240	210
		b	257	270	270	280
		c	107.5	110	110	115.5
		ca	151.5	155	155	160
		bb	194	200	200	243
		aa	44 88	58 116	58 116	70
		d	7	7	7	7

**CẦU DAO TỰ ĐỘNG MCCB
MOULDED CASE CIRCUIT BREAKER**

Frame size (AF)		800	1000	1250	1600	
Model		NF800-SM	NF1000-HM	NF1250-HM	NF1600-HM	
Apperance						
Rated current In (A) at ambient temp. 40°C		700,800	1000	1250	1600	
Rate Insulation Voltage Ui (V)		800	800	800	800	
Number of poles (P)		3 4	3	3	3	
Rated breaking capacity (kA)	IEC 60947-2 EN 60947-2 CNS 14816-2 Icu/lcs AC	440V	42/21	85/43	85/43	85/43
		380V	50/25	100/50	100/50	100/50
		220V	85/43	130/65	130/65	130/65
Dimension (mm)		a	210 280	210	210	210
		b	280	330	330	330
		c	115.5	137	137	137
		ca	160	191	191	191
		bb	243	300	300	300
		aa	70 140	70	70	70
		d	7	9	9	9